



GENERAL SPECIFICATIONS

INSTALLATION: Fencing is erected in accordance with a unique site installation plan, ensuring straight fence lines or smoothly flowing curves, with top of posts following profile of the ground, set rigid and plumb to retain perimeter integrity.

POST SYSTEM: RHS at 2.440m centres, panel fixed to posts with 40 x 6mm slotted clamp bar and M8 cup square bolt and permacone.

PANEL WIDTH: 2.5m.

MESH APERTURE: 76.2mm x 12.7mm.

WIRE DIAMETER: 4mm horizontal, 4mm vertical.

FINISH: Galvanised or galvanised and powder coated to BS EN 13438 in a range of colours to suit your individual requirements.

FENCE Ht (m)	POST SECTION RHS	NUMBER OF FIXINGS	FIXING TYPE
1.80	60x60x3.0	9	NK M8 cup square bolts and tamper-resistant permacone
2.10	60x60x3.0	10	NK M8 cup square bolts and tamper-resistant permacone
2.40	60x60x3.0	11	NK M8 cup square bolts and tamper-resistant permacone
2.70	80x80x3.0	12	NK M8 cup square bolts and tamper-resistant permacone
3.00	80x80x3.0	13	NK M8 cup square bolts and tamper-resistant permacone

* All dimensions represent nominal values.

KEY FEATURES: The ultimate deterrent, providing the highest degree of physical perimeter protection with high density mesh, resulting in a police approved fencing system which is difficult to penetrate or scale.

POLICE APPROVED SPECIFICATION



CERTIFICATION STANDARD: This fencing system complies with the requirements of LPS 1175: "Secured by Design" and is certified by the Loss Prevention Certification Board (LPCB).

GATES: NK Automated Cantilever Sliding Gates are also available to compliment your access control solution.

OTHER PRODUCTS:

- ▶ NK Ibox Vogue
- ▶ NK Ibox Elite
- ▶ NK Ibox Supreme
- ▶ NK Ibox Premier Plus
- ▶ NK Ibox Premier
- ▶ NK Ibox Security

STANDARD COLOUR RANGE

The colours shown are indicative colours. No guarantee can be given that the match is correct.

BLACK
RAL 9005

GREY
RAL 7037

BLUE
RAL 5010

WHITE
RAL 9010

GREEN
RAL 6005

RED
RAL 3000

YELLOW
RAL 1006

BROWN
RAL 8019